

MERCURY EQUIPMENT RESOURCE CATALOG



FORKLIFT CRANES



TELESCOPING BOOM WITH
MAXIMUM HORIZONTAL REACH OF 12
FEET

AVAILABLE IN CAPACITIES OF 3,000, 4000,
6000, AND 8000 LBS

MODEL	MAXIMUM CAPACITY @ HOOK POSITION (LBS)							WEIGHT OF CRANE UNIT
	3'-6"	7'	8'	9'	10'	11'	12'	
PB-30	3000	3000	2600	2200	1900	1600	1500	350 LBS
PB-40	4000	3200	2600	2200	1900	1600	1500	350 LBS
PB-60	6000	5000	4200	3500	3000	2700	2500	420 LBS
PB-80	8000	7000	5700	4800	4100	3600	3100	540 LBS

ROLLING FLOOR CRANES

4 POSITION TELESCOPIC BOOM

PROOF TESTED TO 150% OF CAPACITY

MODEL	BOOM POS. (IN)	CAP. (LBS)	HOOK HEIGHT		O.A. DIMENSIONS (IN)		
			MIN	MAX	L	W	H
B-1000	46-3/8	1000	33"	103"	53-1/8	35-7/8	71-7/8
	52-3/8	750	29-1/2"	107"			
	58-1/4	450	23-1/2"	113"			
	64-1/4	200	15"	122"			
B-2000	57-1/2	2000	29"	98-1/2"	69-3/4	32-1/4	67-1/4
	68-1/2	800	23-1/2"	106"			
	78-3/4	400	17"	114"			
	89-1/2	300	10"	121"			
B-3000	63-3/4	3000	39"	105"	79	35	76
	74-1/4	1200	34-1/2"	112-1/2"			
	85	700	30"	120"			
	95-1/2	500	25"	127"			



EXCEEDS ASME PALD-12 AND ASNI Z535
STANDARDS

SAFETY BY-PASS VALVE IS STANDARD TO
PREVENT DANGEROUS OVERLOADING