

# Fixed Dock Ladders

Built with tough, all-weld construction for years of service, Walk-Thru and Side Step ladders provide easier access to docks, platforms and mezzanines. The Walk-Thru model features a handrail extending 42" above the top rung to help guide you safely up and down. The Side Step has 4 ladder rungs at the top for easy movement up and down. Both ladders rest 6" away from mounting surface for foot clearance when climbing. 300lb capacity. Rigid 1" diameter tubing for handrails. 19" wide steps. One-diamond Grip Strut tread for slip-resistant footing. Meets OSHA standards.



DT4

DT LADDER	# Of Steps	Top Step Height	Wt. Lbs.	EGA #	Lead Times Days
	2	1' 6"	43	DT2	5
	3	2' 6"	46	DT3	5
	4	3' 6"	53	DT4	5
	5	4' 6"	58	DT5	5
	6	5' 6"	66	DT6	5
	7	6' 6"	71	DT7	5
	8	7' 6"	76	DT8	5
	9	8' 6"	80	DT9	5
	10	9' 6"	86	DT10	5

DS LADDER	# Of Steps	# Of Steps & Rungs	Overall Length	Wt. Lbs.	EGA #	Lead Times Days
	2	6	5' 6"	43	DS2	5
	3	7	6' 6"	46	DS3	5
	4	8	7' 6"	53	DS4	5
	5	9	8' 6"	58	DS5	5
	6	10	9' 6"	66	DS6	5
	7	11	10' 6"	71	DS7	5
	8	12	11' 6"	76	DS8	5
	9	13	12' 6"	80	DS9	5
	10	14	13' 6"	86	DS10	5



DS6

### Shipping Info

Starting Zip	Freight Class
53005 or 28115	All Steps 70 to 85

# Wall-Mount Walk-through Steel Dock Ladder

\*500 lbs. rated capacity  
\*Meets OSHA requirements

Our highest weight capacity dock ladder. All welded 1-1/16 steel tube construction. Durable Yellow powder coated. Rungs are 18" wide. Hand rails continue 42" beyond top rung and are capped with red vinyl hand grip. 8" for toe clearance. Mounting brackets have 3/8" mounting hole. (Fastening hardware not included)



WALL-MOUNT WALK-THROUGH STEEL DOCK LADDER	# Of Rungs	Rung Height	Overall Length	Wt. Lbs.	EGA #	Lead Times Days
	3	2'2"	5'8"	27	RT-3	5
	4	3'2"	6'8"	31	RT-4	5
	5	4'2"	7'8"	36	RT-5	5
	6	5'2"	8'8"	43	RT-6	5
	7	6'2"	9'8"	47	RT-7	5
	8	7'2"	10'8"	52	RT-8	5
	9	8'2"	11'8"	56	RT-9	5
	10	9'2"	12'8"	64	RT-10	5

# Two Step Wall-Mount Ladder

\*Grip Strut Treads  
\*Meets OSHA requirements

All welded steel construction. Treads are 18" wide grip strut for traction and self-cleaning. Better for slippery or wet conditions. Four mounting holes for secure fastening to wall. Painted EGA grey enamel. Tread rise is 12". 300lb capacity.



TWO STEP WALL-MOUNT LADDER	# Of Steps	Dimensions	Grip Strut®	
			EGA #	Lead Times Days
2	18"x24"	WML	5	