High performance

Justrite® Sure-Grip® EX

Safety Cabinets are OSHA

compliant, meet NFPA Code

30 and are independently

tested and approved by FM.

- Double-wall construction with 1½" (38mm) insulating air space
- Sturdy 18-gauge (1mm) steel, welded for strength, long life and greater fire protection
- Exclusive U•Loc™ handle includes two keys and accepts an optional padlock for convenience and security. Easy fingertip operation with slip resistant grip for greater control.
- Three-point, stainless steel bullet self latching system for optimum longevity with increased heat resistance
- Rounded safety corners on doors
- 2" (51mm) leakproof sump to capture spills
- Exclusive Haz-Alert[™] reflective warning labels
- Dual 2" (51mm) vents with flame arresters
- Exclusive SpillSlope[™] shelves adjustable on
 3" (76mm) centers
- Durable lead-free powder paint finish, inside-and-out, for maximum chemical resistance
- Four adjustable leveling feet provide a wobble-free base
- Built-in grounding connector prevents static buildup
- Self-close style features fusible links to hold doors open and patented, concealed self-close mechanism for obstruction-free access
- Quality backed by an industry 1st, Ten-Year Warranty

Approval/ Listing and Regulation Key

FΜ

FM Global tested and approved

UL/ULC

Underwriters Laboratories listed in the U.S. and Canada

ΤÜV

TÜV Technical Inspection Association Certified

N

Designed in accordance with National Fire Protection Association (NFPA) Code 30 regulation

0

Complies with OSHA regulations

П

Complies with either the International Fire Code or NFPA 1 Fire Code

EPA

Complies with the Environmental Protection Agency (EPA) regulations

SPCC

Complies with Spill Prevention, Control and Countermeasures Rule





2450 W. Silver Spring Dr. Milwaukee, WI 53209

> Phone: (414) 616-6680 Fax: (414) 616-6696

8





Industry-leading Justrite Safety Cabinets provide the best possible flammable liquid storage and protection.

Justrite's Sure-Grip® EX safety cabinets offer exclusive features to make your workplace EXtra safe, EXtra secure. Distinguishable differences including our U·Loc™ padlockable handle, Haz-Alert™ reflective warning labels, sturdy SpillSlope™ shelves, 3-point stainless steel bullet self-latching system and welded construction help reduce fire risks while offering added convenience and safety. High performance, long-life design is backed by an industry first Ten-Year Warranty!

Protect workers, reduce fire risks, and improve productivity by storing hazardous liquids in code compliant safety cabinets. Designed to meet OSHA and NFPA standards, Justrite's cabinets are sturdily constructed of all-welded, 18-gauge (1mm), double-walled steel with 1¹/2" (38mm) of insulating air space for fire resistance. Exclusive U•Loc™ handle comes with a double key set and/or accepts an optional padlock for security features such as different keying or master keying. Paddle handle with slip resistant strip offers easy fingertip operation and reduces dangerous "catches" from passing traffic. Fail-safe closing mechanism ensures three-point stainless steel bullet latching system works the first time, every time.

Exclusive Haz-Alert™ reflective labeling provides high visibility under fire conditions or power outages. Strategically zone positioned to be firefighter friendly. Exclusive SpillSlope™ galvanized steel shelves safely direct incidental spills to back and bottom of leaktight, 2" (51mm) bottom sump. Adjustable on 3" (76mm) centers for versatile storage, they meet ANSI standards with a 350lbs. (159kgs) safe allowable load. Other extras include dual vents with flame arresters, four adjustable leveling feet, and a grounding connector. Fully painted inside-and-out with a durable lead-free epoxy/polyester powder paint for chemical resistance.

All models are fully compliant to OSHA and NFPA and most are FM Approved. Self-close models also meet the International Fire Code and NFPA 1, Fire Code™. They shut and latch automatically when fusible links melt at 165°F (74°C) under fire conditions. Patented, concealed closing mechanism offers "obstruction-free" access to contents and minimizes risk of damage to the mechanism.

Sure-Grip® EX Safety Cabinets - All Purpose, Yellow

			• •					
Capacity	No. of Doors	Type of Doors	Dimensions H X W X D (mm)	No. of Shelves	Approv./Lstg. Regulation*	Ship Wt. Lbs./Kgs.	Model No.	
30 Gal./114L	2	Manual	44" x 43" x 18" (1118 x 1092 x 457)	1	FM,N,O	221/100	893000	
30 Gal./114L	2	Self-close	44" x 43" x 18" (1118 x 1092 x 457)	1	FM,N,O,U	223/101	893020	
30 Gal./114L	2	Manual	35" x 36" x 24" (889 x 914 x 610)	1	FM,N,O	204/93	893300	_
30 Gal./114L	1	Sliding, self-close	44" x 43" x 18" (1118 x 1092 x 457)	1	FM,N,O,U	246/112	893080	New
45 Gal./170L	2	Manual	65" x 43" x 18" (1651 x 1092 x 457)	2	FM,N,O	299/136	894500	
45 Gal./170L	2	Self-close	65" x 43" x 18" (1651 x 1092 x 457)	2	FM,N,O,U	301/137	894520	_
45 Gal./170L	1	Sliding, self-close	65" x 43" x 18" (1651 x 1092 x 457)	2	FM,N,O,U	301/137	894580	New
60 Gal./227L	2	Manual	65" x 34" x 34" (1651 x 864 x 864)	2	FM,N,O	366/166	896000	
60 Gal./227L	2	Self-close	65" x 34" x 34" (1651 x 864 x 864)	2	FM,N,O,U	368/167	896020	
60 Gal./227L	1	Sliding, self-close	65" x 34" x 34" (1651 x 864 x 864)	2	FM,N,O,U	374/170	896080	New
90 Gal./341L	2	Manual	65" x 43" x 34" (1651 x 1092 x 864)	2	FM,N,O	421/191	899000**	
90 Gal./341L	2	Self-close	65" x 43" x 34" (1651 x 1092 x 864)	2	FM,N,O,U	423/192	899020 **	
90 Gal./341L	1	Sliding, self-close	65" x 43" x 34" (1651 x 1092 x 864)	2	FM,N,O,U	480/218	899080**	New

^{**} Codes state that not more than 60 gallons may be Class I and Class II liquids.

Extra Accessories

	Dimensions	Fits	Ship Wt.	Model
Description	W X D (mm)	Cabinet sizes (mm)	Lbs./Kgs.	No.
SpillSlope™ Steel Shelf	39 ³ / ₈ " x 14" (1000 x 356)	30 & 45 Gal - 43" W (1092)	10/5	29937
SpillSlope™ Steel Shelf	32 ³ / ₈ " x 20" (822 x 508)	30 Gal - 36" W (914)	12/5	29942
SpillSlope™ Steel Shelf	30 ³ / ₈ " x 29" (771 x 737)	60 Gal - 34" W (864)	16/7	29944
SpillSlope [™] Steel Shelf	39 ³ /8" x 29" (1000 x 737)	90 Gal - 43" W (1092)	21/9	29945



896020

